





## Bilge Blowers

The SEAFLO 3" dual-mount blower is designed to provide ventilation for bilges, engine compartments, galleys and heads. The rugged continuous-duty motor and corrosion-resistant ABS housings offer maximum durability in marine applications. The centrifugal fan design provides up to 130 CFM of air flow. SEAFLO blowers provide higher flow, quieter operation and lower current draw than competing blowers. This blower allows for dual mounting methods, flange-mount and flex-mount. The flange mount is when the blower is mounted using the outlet mounting flange to secure the pump. The flex mount is when the motor mounting bracket is used to secure to blower, hose would have to be connected to both the inlet and outlet.



Flange Mount



Flex Mount

Technical Data					N. W./G. W. (kg)	
Model	Volts (V)	Air Flow (cfm/cm <sup>h</sup> )	Amp Draw (A)	Fuse (A)	Packing Size (mm)	
SFB81-130-01	12V	130/220	2.5	5	160*160*200	0.71/0.83
SFB82-130-01	24V	130/220	1.5	3	160*160*200	0.71/0.83





## Features & Benefits

- 4 Year Warranty
- Dual Mounting Options
- Efficient high volume air flow
- Very low current draw, long life
- Flex Mount or Flange Mount
- Sealed motor shaft for moisture protection
- Corrosion resistant ABS plastic housing
- Ignition protected
- CE conforms with EN 50014-1, EN N 61000-3-3

## Typical Applications

- Boats bilge ventilation
- Engine compartments
- Galleys and heads



## SEAFLO Fuel Cans

Fuel Container Gasoline, Diesel, Two-stroke engine oil EAP & AS/NZS 2906:2001 Standards

## Description


Seaflo 5, 10 & 20 Liter automatic shut off fuel cans which are designed with specially proportioned rear handle for balanced pouring that is self venting for safer & easier pouring. Features reduced emissions to protect the environment and meets EAP & AS/NZS 2906:2001 Standards

## Typical Applications

Car, lawnmower, ATV or snowblower, boat dirt bike, go kart, and other essential equipment topped off with fuel

## Features

- Complies to EPA & CARB Standards
- Spill Proof, Durable Vented Pouring Spout
- UV Stabilized High Grade Polyethylene
- Certified to Australian Standard AS/NZS 2906:2001



Model	Capacity	Length	Width	Height	Weight (DRY)	Fuel	Color	Handle Type
SFGT-05-01	5L	260MM	130MM	275MM	0.8KG	Gasoline	Red	Built-in
SFGT-10-01	10L	290MM	160MM	346MM	1.3KG	Gasoline	Red	Built-in
SFGT-20-01	20L	330MM	190MM	476MM	1.8KG	Gasoline	Red	Built-in
SFDT-05-01	5L	260MM	130MM	275MM	0.8KG	Diesel	Yellow	Built-in
SFDT-10-01	10L	290MM	160MM	346MM	1.3KG	Diesel	Yellow	Built-in
SFDT-20-01	20L	330MM	190MM	476MM	1.8KG	Diesel	Yellow	Built-in
SF2T-05-01	5L	260MM	130MM	275MM	0.8KG	Two-stroke Gasoline Engine Oil	Green	Built-in
SF2T-10-01	10L	290MM	160MM	346MM	1.3KG	Two-stroke Gasoline Engine Oil	Green	Built-in
SF2T-20-01	20L	330MM	190MM	476MM	1.8KG	Two-stroke Gasoline Engine Oil	Green	Built-in

Consult factory for other available models